

FIRST.. BEST.. ALWAYS!

EZ-P & P SERIES

EZ-Coil® Model	Model	I.D.	Length	P.S.I.	Max Temp (°F)	W x H x L	Weight
EZ-P-LP-150	P-LP-150	1/4"	50'	300	150	6 1/8" x 18 1/4" x 17 1/4"	40
EZ-P-LP-350	P-LP-350	3/8"	50'	300	150	6 1/8" x 18 1/4" x 17 1/4"	43
-	P-MP-320	3/8"	20'	3000	250	7" x 18 1/4" x 17 1/4"	46
-	P-MP-335	3/8"	35'	3000	250	7" x 18 1/4" x 17 1/4"	52

P Series spring driven hose reels have a long history of dependability and trouble free performance

- Compact space saving design
- Swivel seals: NITRILE
- Heavy gauge 1/4" steel base & support post
- Factory-matched cartridge-style spring motor
- Brass NPT swivel inlet machined from solid
- 1" solid steel axle with 1" lubricated precision bearings

EZ-SH & SH SERIES EQUIPPED WITH SUPER HUB™

EZ-Coil® Model	Model	I.D.	Length	P.S.I.	Max Temp (°F)	W x H x L	Weight
EZ-SH-435	SH-N-435	1/2"	35'	300	150	9 1/4" x 21" x 19 5/8"	49
EZ-SH-450	SH-N-450	1/2"	50'	300	150	9 1/4" x 21" x 19 5/8"	54
-	MP-N-350	3/8"	50'	3000	250	8 3/4" x 21" x 19 5/8"	65
-	MP-N-435	1/2"	35'	2500	250	9 1/4" x 21" x 19 5/8"	61
-	MP-N-450	1/2"	50'	2500	250	9 1/4" x 21" x 19 5/8"	67
-	HP-N-335	3/8"	35'	4000	250	9 1/4" x 21" x 19 5/8"	61
-	HP-N-350	3/8"	50'	4000	250	9 1/4" x 21" x 19 5/8"	65

SH Series are larger chassis and frame to accommodate larger hoses

- Equipped with Super Hub™ featuring two support points to the center shaft
- 1" solid steel axle with 1" lubricated precision bearings
- Super Hub™ dual axle support system increases the stability during operation, reduces vibration and strengthens the structural integrity of the reel.

EZ-T & T SERIES EQUIPPED WITH SUPER HUB™

EZ-Coil® Model	Model	I.D.	Length	P.S.I.	Max Temp (°F)	W x H x L	Weight
EZ-TSH-3100	TSH-N-3100	3/8"	100'	300	150	9 1/4" x 25 1/2" x 23"	85
EZ-TSH-475	TSH-N-475	1/2"	75'	300	150	9 1/4" x 25 1/2" x 23"	82
EZ-TSH-550	TSH-N-550	3/4"	50'	300	150	9 3/4" x 25 1/2" x 23"	83
-	TDMP-N-350	3/8"	50'	3000	250	10 3/4" x 25 1/2" x 23"	104

T Series are larger chassis and frame to accommodate larger hoses

- Equipped with Super Hub™ featuring three support points to the center shaft
- 1" solid steel axle with 1" lubricated precision bearings
- Super Hub™ dual axle support system increases the stability during operation, reduces vibration and strengthens the structural integrity of the reel.

EZ-SHW & SHW SERIES

EZ-Coil® Model	Model	I.D.	Length	P.S.I.	W x H x L	Weight
EZ-SHWL-150	SHWL-N-150	1/4"	50'	200	10 7/8" x 21" x 19 5/8"	52

SHW series reels are an ideal solution for managing bulky twin line welding hose

- Designed for Oxy-Acetylene or "T" Grade welding hose
- Dual ported swivel offers both connections from the same side of the reel
- Applications include: MAPP Gas, Propane & Natural Gas
- Swivel lock bracket ensures maximum safety
- Swivel seals: Viton


EZ-PC & PC SERIES

All of our PC Series reels are available with 100'

EZ-Coil® Model	Model	Accessories	AWG.	# Cond. • Ft	W x H x L	Amps	Weight
EZ-PC13-3512-B	PC13-3512-B	Quad Industrial Receptacle	12	3 • 35'	8 1/2" x 14 1/2" x 13 3/4"	20	38
EZ-PC13-5012-B	PC13-5012-B	Quad Industrial Receptacle	12	3 • 50'	8 1/2" x 14 1/2" x 13 3/4"	20	41
EZ-PC13-5016-C	PC13-5016-C	Fluorescent Tube Light	16	3 • 50'	8 1/2" x 14 1/2" x 13 3/4"	13	37
EZ-PC13-5016-D	PC13-5016-D	Fluorescent Angle Light / w tool tap	16	3 • 50'	8 1/2" x 14 1/2" x 13 3/4"	13	37
EZ-PC24-0016-D	PC24-0016-D	Fluorescent Angle Light / w tool tap	16	3 • 50'	9 3/4" x 25 1/4" x 23"	13	73
-	PC13-5012-F	Duplex G.F.C.I Metal Industrial Receptacle	16	3 • 100'	8 1/2" x 14 1/2" x 13 3/4"	13	42

PC Series spring driven "Power Cords" reels are heavy duty, industrial grade power sources

- Includes 5' pigtail & grounding plug (Except on less hose models)
- Heavy gauge powder coated steel components cover
- Choice of electrical accessories
- 1" solid steel axle with 1" lubricated precision bearings
- Factory-matched cartridge-style spring motor



W D

WHOLESALE DIRECT inc.




EZ-P & P Series



EZ-SH & SH Series



EZ-T & T Series



EZ-SHW & SHW Series



EZ-PC13 & PC13 Series

www.wholesaledirectinc.com



COXREELS®

Your Reel Source



5620 West 65th Street, Chicago, IL 60638-5502

Tel: (773) 585-7200