



Wholesale Direct Inc.

5620 West 65th Street Chicago, IL 60638

Phone (773) 585-7200 Fax (773) 585-7279 Toll Free (888) 250-1700

www.wholesaledirectinc.com



238DB Drawbar Eye

This eye allows for a easy horizontal bolt on application.

Specifications:

Max GTW: 90,000 lbs.
Max Tongue Wgt: 8,000 lbs.
Inside Diameter: 3 in.



135NT Swivel Coupling

Utility companies, construction, agriculture and military operations will all benefit from this swivel coupling. Swivel action eliminates torque between mated vehicles when traveling over rough, uneven terrain. (NOT to be used with a swivel-type drawbar eye.)

Specifications:

Max Gross Trailer Weight: 30,000 lbs.
Max Tongue Weight: 6,000 lbs.
Ultimate Latch Capacity: 20,000 lbs.
Max Eye X-Section: 1 11/16 in.
Min Eye Opening: 2 1/16 in.

PREMIER MANUFACTURING CO.



235NT Swivel Coupling

Premier's 235NT Swivel is a bit heavier duty than our 135NT Swivel for those extra tough jobs. When rough uneven ground is a problem, the 235NT Swivel may be the answer. (NOT to be used with a swivel-type drawbar eye.)

Specifications:

Max Gross Trailer Weight: 60,000 lbs.
Max Tongue Weight: 12,000 lbs.
Ultimate Latch Capacity: 20,000 lbs.
Max Eye X-Section: 1 11/16 in.
Min Eye Opening: 2 1/8 in.



150 Combo Coupling


One of our most unique and versatile couplings. Whether you need to pull a trailer with an eye or ball connection, the 150 can do the job. Our patented side-swing latch helps prevent tailgate damage and keeps the profile compact.

Specifications:

Max Gross Trailer Weight: 16,000 lbs.
Max Tongue Weight: 2,000 lbs.
Ultimate Latch Capacity: 5,000 lbs.
Max Eye X-Section: 1 13/16 in.
Min Eye Opening: 2 3/8 in.

Ball Capacities:

150 w/2 in. Ball: MGTW: 10,000 lbs.
150 w/2-5/16 in. Ball: MGTW: 10,000 lbs.
150 w/1-7/8 in. Ball: MGTW: 2,500 lbs.



165 Receiver

Designed for superior strength, the 165 is a one-piece, solid steel casting, adjustable mount for 2 in. receiver-type connections. It allows for three different vertical height positions for mounting Premier's 150 & 160 couplings.

Specifications:

Max Gross Trailer Weight: 10,000 lbs.
Max Tongue Weight: 1,000 lbs.
Pin Diameter: 5/8 in.



166 Receiver

The 166 Receiver is also a single, solid steel casting, adjustable mount receiver, except it is used in 2 1/2 in. receiver-type connections. It allows for three different vertical height positions for mounting Premier's 150 & 160 couplings.

Specifications:

Max Gross Trailer Weight: 12,000 lbs.
Max Tongue Weight: 1,200 lbs.
Pin Diameter: 5/8 in.



Wholesale Direct Inc.

5620 West 65th Street Chicago, IL 60638

Phone (773) 585-7200 Fax (773) 585-7279 Toll Free (888) 250-1700

www.wholealedirectinc.com



200 Bolt-On Eye

This eye features a 2-3/8" inside diameter (ID) loop and is one of our most popular eyes. It allows for an easy and secure connection on vertical oriented mounting structures.

Specifications:

Max GTW: 100,000 lbs.
Max Tongue Wgt: 15,000 lbs.
Inside Diameter: 2 3/8 in.



300 Bolt-On Eye

This eye has the same popularity and ease of install as our model 200 but features a larger inside diameter eye loop for those applications that need a larger eye loop.

Specifications:

Max Gross Trailer Weight: 100,000 lbs.
Max Tongue Weight: 15,000 lbs.
Inside Diameter: 3 in.

PREMIER MANUFACTURING CO.



240 Coupling

Designed as a direct retrofit to the mounting pattern of Premier's 135NT Swivel Coupling. The 240 has extra toughness and wear resistance that Premalloy users have come to expect.

Specifications:

Max Gross Trailer Weight: 45,000 lbs.
Max Tongue Weight: 6,000 lbs.
Ultimate Latch Capacity: 20,000 lbs.
Max Eye X-Section: 1 11/16 in.
Min Eye Opening: 2 1/16 in.



2200 Air Adjusted Coupling

Features the most popular mounting bolt pattern in the industry. Exceptional latch strength, easy operation and low maintenance. All 2000 series couplings can be operated with or without an air service chamber.

Specifications:

Max Gross Trailer Weight: 100,000 lbs.
Max Tongue Weight: 20,000 lbs.
Ultimate Latch Capacity: 60,000 lbs.
Max Eye X-Section: 1 13/16 in.
Min Eye Opening: 2 3/8 in.



600 Jiffy Jack

Our 600 Series Jiffy Jack out performs any other jack in its class. Unique "Jiffy Quick Release" for instant, one-lever lowering and retracting of the leg without cranking.

Specifications:

Capacity: 5,000 lbs. operational
10,000 lbs. static



700 Custom Jack

The Premier 700 Custom Jack has been engineered and built to the same stringent specifications as our 600. Designed for long life with minimal maintenance, the 700 is easily adapted to nearly any application.

Specifications:

Capacity: 5,000 lbs. operational
10,000 lbs. static