

824 MULTI STROBE

Medium Profile - Double or Quad Flash

Model 824-1228

(Amber, Blue, Clear, Green or Red)
(6.75" tall x 5.5" dia. x 2.2lbs)

Accessory: G800 - Heavy Duty Guard

The model 824 family is a medium profile, multi-flash strobe light which can be changed by the customer from double flash to quad flash operation. It features universal mounting, full size 360° Lexan® lens, hi-efficiency regulated solid state power supply, and heavy duty xenon strobe lamp. DC units have polarity protection and built-in filters to protect against radio interference and spike voltages. AC units are designed to withstand multiple line transient spikes of 6000V without damage. The model 824 strobe features a fully potted, Lexan®, multi-purpose mounting base which is vibration and water resistant, and has a plug-in strobe lamp and photocell which can be activated to automatically reduce intensity during nighttime operation.



MICRO IV

Low Profile - Single Flash Strobe

470S-1280 (Surface Mount)

485S-1280 (Screw-in Light bulb base)

490S-1280 (1/2" female pipe mount)

495S-1280 (1/2" male thread mount)

(Amber, Blue, Clear, Green or Red)
(5" tall x 3" dia. x 0.6 lbs)

The MICROSTROBE® family is a low profile, single flash, low cost strobe light which features a plug-in replaceable lamp, all Lexan® lens, rain tight construction, and a hi-efficiency solid state power supply. All units are polarity protected and have built-in filters to protect against radio interference.



RECT25

LOW-PROFILE LED SERIES
WITH PROGRAMMABLE INTERNAL FLASHER

- Choice of mounts: (standard mount = 5.5" wide x 1.97" high x 1.36" deep)
(rail mount = 6.25" wide x 1.97" high x 1.36" deep)
- Choice of output (HP - High Power, SD - Std. Power, or LC - Low Current)
- Choice of Finish (aluminum or black)



200s

Low Profile - LED Series
With Programmable Internal Flashers

- Choice of mounts (standard mount = 10.1" wide x 1.97" high x 1.36" deep)
(rail mount = 10.85" wide x 1.97" high x 1.36" deep)
- Choice of output (HP - High Power, SD - Std. Power, or LC - Low Current)
- Choice of Finish (aluminum or black)



200Series

Low Profile Arrow Sticks - LED Series

200-6 Amber Arrow Systems

TD-LED-LC-6

TD-LED-SD-6

(standard mount = 29.25" wide x 1.97" high x 1.36" deep)
(rail mount = 28.55" wide x 1.97" high x 1.36" deep)

200-8 Amber Arrow Systems

TD-LED-LC-8

TD-LED-SD-8

(standard mount = 38.45" wide x 1.97" high x 1.36" deep)
(rail mount = 37.75" wide x 1.97" high x 1.36" deep)

Systems include 930L-24-200 arrow flashers



Designed with the latest in LED technology, TOMAR's newest line of products provides a sleek low-profile look with extreme light output. Our latest LED designs are based on TIR (Total Internal Reflection) technology and provide unprecedented off-center visibility and a unique thermal management system that utilizes the entire housing to draw heat away from the LEDs for longer life and more consistent light output. Experience in-person, the brilliant output and performance of TOMAR's new line of LED products.



TOMAR Electronics, Inc.
Clearing the Way